IT6831 18V / 10A / 180W





IT6831 18V / 10A / 180W

Compact, affordable programmable Power supply

The IT6800-series of programmable dc power supplies give you the performance of system power supplies without the high price. All models give you clean power, dependable regulation and programmable with GPIB, USB and RS-232 interface. IT6800series are designed to meet the most demanding applications with high performance and reliability you can count on

Feature

- Liner Programmable Power supply
- USB/GPIB/RS232 Interface
- Intellective fan cooling
- VFD Display
- SCPI Compatible

Specifications

- Low noise and ripple output
- CV / CC Mode
- ½2U Standard 19" rack or bench top install
- Convenient numeric keypad
- Over current and temperature protection

| Output Ratings | Voltage | 0-18V |
|---------------------|-------------|---|
| | Current | 0-10A |
| Load Regulation | Voltage | < 0.02% + 5 mV |
| | Current | < 0.01% + 3mA |
| Line Regulation | Voltage | < 0.01% + 3 mV |
| | Current | <0.1%+2mA |
| Setup Resolution | Voltage | 10mV |
| | Current | 10mA |
| Setup Accuracy | Voltage | $\leq 0.05\% + 10 \text{mV}$ |
| | Current | ≤0.2%+10mA |
| Readback Resolution | Voltage | $10 \text{mV} (<\!20 \text{V}) / 100 \text{mV} (\geq\!20 \text{V})$ |
| | Current | 10mA |
| Readback Accuracy | Voltage<20V | < 0.05% + 15 mV |

Voltage<20 V ≤0.05%+15mV Voltage≥20V $\leq 0.05\% + 120 \text{mV}$ Current <0.1%+15mA Ripple(20-20MHz) Voltage

 $\leq 0.5 \text{mVrms/} 3 \text{mVp-p}$

Current ≤5mArms

Temperature Operating 0 to 40 ≤ 75 R.H. -15 to 70 Storage \leq 85 R.H.

Dimension W*H*D(mm)214.5 * 88.2 * 354.6

Weight Net 8.5Kg

Standard Accessories

- AC Line Cord
- USER Manual
- Calibration Report

Optional Accessories

- IT-E131 RS232 Communication Cable
- IT-E132 USB Communication Cable
- IT-E133 GPIB Communication Cable
- IT-E151 19" Rack Mount Kit