

IT6832 32V / 6A / 192W



IT6832 32V / 6A / 192W

Voltage

Current

Voltage Current

Voltage

Current

Voltage

Current

Voltage Current

Voltage

Current

Current

Voltage

Current

Storage

Net

Operating

W*H*D(mm)

Voltage<20V

Voltage≥20V

Compact, affordable programmable Power supply

The IT6800-series of programmable dc power supplies give you the performance of system power supplies without the high price. All models give you clean power, dependable regulation and programmable with GPIB, USB and RS-232 interface. IT6800-series are designed to meet the most demanding applications with high performance and reliability you can count on

Feature

- Liner Programmable Power supply
- USB/GPIB/RS232 Interface
- Intellective fan cooling
- SCPI Compatible
- VFD Display

Specifications

Output	Ratings
--------	---------

Load Regulation

Line Regulation

Setup Resolution

Setup Accuracy

Readback Resolution

Readback Accuracy

Ripple(20-20MHz)

Temperature

Dimension Weight

Standard Accessories

- AC Line Cord
- USER Manual
- Calibration Report

- Low noise and ripple output
- CV / CC Mode
- ½2U Standard 19" rack or bench top install
- Convenient numeric keypad
- Over current and temperature protection

0-32V 0-6A <0.02%+5mV < 0.01% + 3mA<0.01%+3mV <0.1%+2mA 10 mV10mA $\leq 0.05\% + 10mV$ $\leq 0.2\% + 10 \text{mA}$ 10mV(<20V) / 100mV(≥20V) 10mA ≤0.05%+15mV ≤0.05%+120mV <0.1%+15mA ≤0.5mVrms/3mVp-p ≤5mArms 0 to 40 \leq 75 R.H. -15 to 70 ≤ 85 R.H. 214.5 * 88.2 * 354.6 8.5Kg

- Optional Accessories
 - IT-E131 RS232 Communication Cable
 - IT-E132 USB Communication Cable
 - IT-E133 GPIB Communication Cable
 - IT-E151 19" Rack Mount Kit